

## 鑽孔機 Drilling Machine

### 簡易手壓鑽孔機 Drilling & Tapping Machine

YL-430



※不含鑽頭 Without Drill

型號 MODEL	YL-430
速度 Spindle speeds	6
鑽孔能力 Drilling capacity	13
攻牙能力 Tapping capacity	4-12
旋徑 Swing	360
主軸至床面距離 Distance from spindle nose to table	480
主軸至底面距離 Distance from spindle nose to base	650
主軸斜度 Taper of spindle	JT#2 1/2
主軸行程 Travel of spindle	80
主軸回轉速 SPINDLE SPEED	
50 cycle	240-1760R.P.M.
60 cycle	290-2130R.P.M.
圓柱直徑 Diameter of colum	Ø80
床面面積 Table dimension	Ø320
底座面積 Base dimension	505×305
機械高度 Over high	1050
馬達 Motor	1/2HP 6P/3PH or 1HP 6P/3PH
淨重 N.W	76kgs

### 單軸鑽孔機 Electric Drilling Machine

YL-20



※不含鑽頭 Without Drill

型號 MODEL	YL-20
速度 Spindle speeds	9
鑽孔能力 Drilling capacity	20mm 3/4"
旋徑 Swing	450
主軸至床面距離 Distance from spindle nose to table	625
主軸至底面距離 Distance from spindle nose to base	885
主軸斜度 Taper of spindle	MT#3
主軸行程 Travel of spindle	120
主軸回轉速 SPINDLE SPEED	
50 cycle	210-1620R.P.M.
60 cycle	250-1940R.P.M.
圓柱直徑 Diameter of colum	Ø92
床面面積 Table dimension	Ø400
底座面積 Base dimension	580×330
機械高度 Over high	1460
馬達 Motor	1HP 4P or 2HP 4P
淨重 N.W	120kgs

型號 MODEL	YL-13
速度 Spindle speeds	4
鑽孔能力 Drilling capacity	13mm (1/2")
旋徑 Swing	360 mm
主軸至床面距離	480 mm
主軸至底座距離	650 mm
Distance from spindle nose to table	
主軸斜度 Taper of spindle	JT#1-1/2
主軸行程 Travel of spindle	80
主軸迴轉速 Spindle speed	460-2040 R.P.M
圓柱直徑 Diameter of column	Ø80
床面面積 Table dimension	Ø320
底座面積 Base dimension	505x305 mm
機械高度 Over high	1050 mm
馬達 Motor	1/4HP 4P or 1/2HP 4P
淨重 N.W	70 kg

### 自動鑽孔座 Automatic Boring Unit YL-010



### 萬能鑽孔座 Universal Boring Unit YL-012



### 臥式鑽孔座 Horizontal boring unit YL-021



型號 MODEL	YL-010	YL-012	YL-021
動力 Power		1HP / 3PH	
回轉速 Running speed	3440R.P.M./60Hz	2000R.P.M. / 60Hz	
行程 Stroke		80mm(3 1/8")	
淨重 N.W.	42kg(96lb)	38kg(86lb)	31kgs

### 鑽孔機 Drilling Machine YL-13

